



4

Watertight surface mounted LED fittings

Properties

Fitting type	Surface mounted
Base	Aluminium, white, grey or black powder coated
Diffuser	Polycarbonate, clear or opaque
Voltage range	<ul style="list-style-type: none"> * 10 - 30 VDC bi-voltage * 230 VAC through an external LED driver/converter (see page 6.02 and 6.03) * automatic switch-over between power supply via external LED driver/converter and battery by use of separate power switch (see page 6.04)
Watertight	Yes (IP66 classification + ADR certified)
Light source	DEMCO LED modules
Light colours	<ul style="list-style-type: none"> * Natural white (4000K, standard colour) * Cool white (6000K) * Warm white (3000K) * other colours on request
Continuous lighting system	No
Switch	No
Motion sensor	Option, integrated in the fitting <ul style="list-style-type: none"> * default delay time after last detection 1 minute * other available delay times are 15 seconds, 5 or 10 minutes
Night light	Option, 6 LED's (blue, red or green), via second positive wire (these versions are not ADR certified)
Dimmable	Option, 2 positions (30 / 100%), via second positive wire

From page 7.02 you will find more technical information.

The specifications in the tables are stated for our regular LED light colour 'natural white' (4000K). The light output of the other 2 LED light colours 'cool white' (6000K) and 'warm white' (3000K) may vary slightly. These specifications are available by request.

Versions (5 - 11W, 10-30 VDC bi-voltage)

Power (Watt)	Voltage (Volt)	Lamp (LED)	Light output (Lumen)	Outside dimension (Ø x H in mm)	Article number (view B D L OO choices)
Power LED (10-30 VDC)					
5	10-30	1 x 3 power LED	600	Ø 155 x 20	DIWTSU B 104 D L OO
8	10-30	1 x 6 power LED	900	Ø 155 x 20	DIWTSU B 105 D L OO
11	10-30	1 x 6 power LED (high output)	1200	Ø 155 x 20	DIWTSU B 124 D L OO
Power LED (10-30 VDC, 2 positions dimmable 30 / 100%)					
5	10-30	1 x 3 power LED	600	Ø 155 x 20	DIWTSU B 112 D L OO
8	10-30	1 x 6 power LED	900	Ø 155 x 20	DIWTSU B 113 D L OO
11	10-30	1 x 6 power LED (high output)	1200	Ø 155 x 20	DIWTSU B 126 D L OO

Article number (**B D L OO** choices)

B = Base	1 = White	2 = Grey	3 = Black
D = Diffuser	H = Clear	O = Opaque	
L = Light colour	1 = Natural white	2 = Cool white	3 = Warm white
OO = Option	00 = No option	40 = LED NL blue	A7 = PIR 15 seconds
		50 = LED NL red	B7 = PIR 1 minute
		60 = LED NL green	D7 = PIR 5 minutes
			E7 = PIR 10 minutes

NL = Night light; PIR = motion sensor (not possible with 2 positions dim or night light)

Example

Article number DIWTSU **2** 105 **H 1 00** results in the following article:

Surface mounted fitting 'Disc WT'

* Ø152x20mm

* 1x6 power LED-8W/10-30VDC

* LED light colour 'natural white'

* light output 900 Lumen

* clear diffuser/grey casing

* watertight IP66, ADR