





Example of wall mounting



Example of ceiling mounting



Properties

Fitting type	Surface mounted
Base	Aluminium, silver or black anodised, white, yellow or red powder coated
Diffuser	Polycarbonate, clear or opaque
End caps	Polycarbonate, white, grey or black, mounted with stainless steel screws
Voltage range	* 10 - 30 VDC bi-voltage * 230 VAC through an external LED driver/converter (see page 6.02 and 6.03) * automatic switch-over between power supply via external LED driver/converter and battery by use of separate power switch (see page 6.04)
Watertight	Yes, IP66 classification
Light source	DEMCO LED modules
Light colour	* Natural white (4000K, standard colour) * Cool white (6000K) * Warm white (3000K) * other colours on request
Continuous lighting system	Yes, custom-made fittings are possible (> approx. 1.6 meter)
Switch	No
Motion sensor	No (see page 6.05 for separate motion sensor)
Night light	No
Dimmable	No

From page 7.02 you will find more technical information.



White powder coated



Black anodised



Silver anodised



Yellow (RAL 1016) powder coated



Red (RAL 3000) powder coated

The specifications in the tables are stated for our regular LED light colour 'natural white' (4000K). The light output of the other 2 LED light colours 'cool white' (6000K) and 'warm white' (3000K) may vary slightly. These specifications are available by request.

Versions (25 - 35W/m, 18 power LED/m, 10-30 VDC bi-voltage)

Power (Watt)	Voltage (Volt)	Lamp (LED)	Light output (Lumen)	Outside dimension (L x W x H in mm)	Article number (view B D E L choices)
Power LED (25W/m, 18 power LED/m, 10-30 VDC)					
4	10-30	1 x 3 power LED	450	260 x 34 x 26	TR60WT B 101 D E L
8	10-30	1 x 6 power LED	900	409 x 34 x 26	TR60WT B 103 D E L
16	10-30	2 x 6 power LED	1800	708 x 34 x 26	TR60WT B 203 D E L
24	10-30	3 x 6 power LED	2700	1007 x 34 x 26	TR60WT B 303 D E L
32	10-30	4 x 6 power LED	3600	1306 x 34 x 26	TR60WT B 403 D E L
40	10-30	5 x 6 power LED	4500	1605 x 34 x 26	TR60WT B 503 D E L
Power LED (35W/m, 18 power LED/m high output, 10-30 VDC) ⚠					
5.5	10-30	1 x 3 power LED	600	260 x 34 x 26	TR60WT B 125 D E L
11	10-30	1 x 6 power LED	1200	409 x 34 x 26	TR60WT B 123 D E L
22	10-30	2 x 6 power LED	2400	708 x 34 x 26	TR60WT B 223 D E L
33	10-30	3 x 6 power LED	3600	1007 x 34 x 26	TR60WT B 323 D E L
44	10-30	4 x 6 power LED	4800	1306 x 34 x 26	TR60WT B 423 D E L
55	10-30	5 x 6 power LED	6000	1605 x 34 x 26	TR60WT B 523 D E L

⚠ Mounting on a metal base is necessary because of the heat sink of the LED's.

Article number (**B D E L** choices)

B = Base	1 = White	4 = Silver	5 = Black
	6 = Yellow (RAL 1016)	7 = Red (RAL 3000)	
D = Diffuser	H = Clear	O = Opaque	
E = End caps	W = White	G = Grey	Z = Black
L = Light colour	1 = Natural white	2 = Cool white	3 = Warm white

Example

Article number TR60WT **4** 203 **H G 2** results in the following article:

Surface mounted fitting 'Track 60 WT'

- * 708x34x26mm
- * base silver anodised
- * 2x6 power LED-16W/10-30VDC
- * LED light colour 'cool white'
- * light output 2200 Lumen
- * clear diffuser/grey end caps
- * watertight IP66

💡 It is also possible to use the 'configurator' on our website to compose the fitting of your choice.